

PDR 908 [EL] / LW

52908354GB / 11105580 / Great Britain

Construction type and design

Linie Professional dryer / Performance Plus
Construction type / Drying system Frontloader, stackable / Elektro (EL)
Compliant with EU Machinery Directive 2006/42/EG Yes

Front Lotus white, enamelled (LW)
Side panels Lotus white, powder-coated
Rear panel Galvanised
Machine lid properties Stainless steel

Load capacity 8,0 kg
Drum volume 130 l

Drum type Honeycomb drum
Inner drum material Stainless steel
Drying system Abluft elektrisch
Coolant
Refrigerant quantity

Door opening [Ø] 370 mm
Door hinge side left
Door openingswinkel in Grad 167 °
Maximum evaporation capacity 4,80 l/h

Performance data - Energy consumption

Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % 0,500 kWh/kg
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % 0,420 kWh/kg

Performance data - Cycle time

Programme duration for Cottons/Normal drying programme with residual moisture at 48 % 52 mins.
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % 57 mins.

Controls

Controls M Touch Flex

Standard electrical connection

Heating Elektro (EL)

Electrical connection 220-230V~ 50HZ
Heater rating 4,780 - 5,220 kW
Total rated load 5,030 - 5,470 kW
Fuse rating 25 A

PDR 908 [EL] / LW

52908354GB / 11105580 / Great Britain

Voltage version 1

Electrical connection

Heater rating

Total rated load

Fuse rating

Voltage version 2

Electrical connection

Heater rating

Total rated load

Fuse rating

Voltage version 3

Electrical connection

Heater rating

Total rated load

Fuse rating

Dimensions and weight

Net Height – Width – Depth

850 mm - 596 mm - 717 mm

Net weight

51,5 kg

Max. floor load in operation

920 N

Gross Height – Width – Depth

940 mm - 660 mm - 820 mm

Gross weight

57 kg

Emissions data

Workplace sound emissions (sound pressure)

<70 dB(A) re 20 µPa

Heat dissipation to installation site

0,76 Mj/h

Efficiency and sustainability

Recycling rate

95 %