

## PWM 507 Hygiene [EL DV] / LW

51507244GB / 11588400 / Great Britain

### Construction type and design

Line Professional washing machine / Performance  
 Construction type / heating Frontloader, stackable / Electric (EL)  
 Compliant with EU Machinery Directive Yes

Front Lotus white, enamelled (LW)  
 Side panels Lotus white, powder-coated  
 Rear panel Galvanised  
 Machine lid properties Lotus white, plastic  
 Outer drum material Stainless steel

Load capacity 7 kg  
 Drum volume 64 l

Drum type Honeycomb drum, perforated rear panel  
 Inner drum material Stainless steel  
 Door opening [Ø] 300 mm  
 Door hinge side Right  
 Door opening angle 167 °

### Performance data - Water consumption

Specific Coloureds 60°C (CW) 7.00 l/kg  
 Coloureds 60°C (CW) 49.0 l  
 Mop Standard 60°C (CW)

Specific Coloureds 60°C (HW) 6.60 l/kg  
 Coloureds 60°C (HW) 46.0 l  
 Mop Standard 60°C (HW)

### Performance data - Energy consumption

Specific Coloureds 60°C (CW) 0.14 kWh/kg  
 Coloureds 60°C (CW) 0.98 kWh  
 Mop Standard 60°C (CW)

Specific Coloureds 60°C (HW) 0.06 kWh/kg  
 Coloureds 60°C (HW) 0.44 kWh  
 Mop Standard 60°C (HW)

### Performance data - Cycle time

Coloureds 60°C (CW) 59 mins.  
 Mop Standard 60°C (CW)

Coloureds 60°C (HW) 49 mins.  
 Mop Standard 60°C (HW)

Residual moisture - Cold rinse 48 %  
 Residual moisture - Hot rinse 45 %  
 Residual moisture - Mops

Spin speed 1600 rpm  
 g-factor - Spin 704  
 Operating hours (tested) 30,000 h

## PWM 507 Hygiene [EL DV] / LW

51507244GB / 11588400 / Great Britain

### Controls

Controls M Select

### Standard electrical connection

Heating Electric (EL)

Electrical connection 230V~  
Heater rating 5.3 kW  
Total rated load 5.5 kW  
Fuse rating 25 A

### Voltage version 1

Electrical connection  
Heater rating  
Total rated load  
Fuse rating

### Voltage version 2

Electrical connection  
Heater rating  
Total rated load  
Fuse rating

### Water connection/drainage

Cold water: 1x 1/2" with 3/4" threaded union  
Hot water 1x 1/2" with 3/4" threaded union  
Water inlet hose - Length 1.55 m  
Drain Drain valve (DV) / Drain connection DN70

### Dimensions and weight

Net Height – Width – Depth 850 mm - 596 mm - 714 mm  
Net weight 101 kg  
Max. floor load in operation 2820 N

Gross Height – Width – Depth 944 mm - 660 mm - 768 mm  
Gross weight 105.4 kg

### Emissions data

Workplace sound emissions (sound pressure) <70 dB(A) re 20 µPa  
Heat dissipation to installation site 1.00 Mj/h

### Efficiency and sustainability

Recycling rate 95 %