Miele PFD 101 Free-Standing Dishwasher

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.

- Wash performance: 13 place settings in just 20min.*
- Everything completely dry – AutoOpen assisted drying
- Intuitive to operate thanks to clear control panel design
- Flexible loading of load items for the best cleaning results

EAN : 4002516446132 / Article no. : 61010110GB / Mat. no. : 11807820

Construction type and version	
Construction type	Freestanding dishwasher
Range	ProfiLine
Wash system	Fresh water
Number of levels	2
Front	Brilliant white
Lid	Plastic
Side panels	Brilliant White
Drying	AutoOpen assisted drying Extra drying Active condensation drying
Application	
Suitable for guesthouses	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for small businesses	•
Suitable for sports clubs	•
Performance data	
Tested virucidal efficacy	•
Circulation pump Qmax in l/min.	75
Shortest programme duration in min.	20
Maximum final rinse temperature in °C	82
Cleaning performance, place settings/cycle	13
Service life in wash cycles	12,500
Controls	
Control system	Electronic controls
Programme selection	Program Selector Buttons
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Filter indicator light	•
Selectable display languages	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	6.10
Total connected load in kW	6.30
Fuse rating in A	32
Length of mains connection cable in m	1.70
Provided with plug	•

For further information see the following pages

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.

Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	1.9
Total connected load in kW	2.10
Fuse rating in A	13
Water connection/drainage	
Cold or hot water [number]	1
Required flow pressure in bar	0,30-10,00
Drain pump [DN]	22
Maximum delivery head for drain pump in cm	100
Integrated water softener	•
Maximum water hardness in mmol/l	6.50
Water protection system	Waterproof system
Length of water inlet hose in cm	150
Length of water drain hose in cm	150
Dimensions and weight	
External dimensions, net height in mm	845
External dimensions with lid, height in mm	845
External dimensions, net width in mm	598
External dimensions, net depth in mm	570
External dimensions, gross height in mm	970
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	670
Usable space in wash cabinet, height in mm	540
Usable space in wash cabinet, width in mm	510
Usable space in wash cabinet, depth of upper basket in mm	450
Usable space in wash cabinet, depth of lower basket in mm	450
In-feed height above floor in mm	210
Net weight in kg	60
Gross weight in kg	67
Maximum floor loading in N	1,000
Emissions data	
Sound power (LwA) in dB(A) re 1 pW	46.0
Programmes	
Universal	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Plastics	•
Energy save/Eco	•
Intensive	•

For further information see the following pages

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.

Basket design	
ExtraComfort baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	2
FlexCare cup rack [number]	1
Cutlery basket	•
Height-adjustable upper basket	•
Features	
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
AutoOpen assisted drying	•
AutoClose	•
EcoFeedback	•
Brilliant GlassCare	•
Safety lock	•
Adjustable final rinse temperature	•
Optical interface	•
SmartStart	•
FlexiTimer with EcoStart	•
Efficiency and sustainability	
Load size of the ECO programme in place settings	13
Energy efficiency class (A–G)	E
Energy consumption of the ECO programme per 100 cycles in kWh	93
Water consumption of the ECO programme per cycle in l	12
Airborne noise emission rating (A–D)	C
Airborne noise emission in dB(A) re 1 pW	46
Programme running time of the ECO programme in min	250
Connection options	
External dispensing module for liquid detergent	•
Test certificate	
CE	•
Complies with Machinery Directive 2006/42/EC	•
VDE	•
EMC radio suppressed	•
EN 1717	•

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.

- Wash performance: 13 place settings in just 36min.*
- Everything completely dry – AutoOpen assisted drying
- Intuitive to operate thanks to clear control panel design
- Flexible loading of load items for the best cleaning results

EAN : 4002516367017 / Article no. : 61010100GB / Mat. no. : 11605560

Construction type and version	
Construction type	Freestanding dishwasher
Range	ProfiLine
Wash system	Fresh water
Number of levels	2
Front	Brilliant white
Lid	Plastic
Side panels	Brilliant White
Drying	AutoOpen assisted drying Extra drying Active condensation drying
Application	
Suitable for guesthouses	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for small businesses	•
Suitable for sports clubs	•
Performance data	
Tested virucidal efficacy	•
Circulation pump Qmax in l/min.	75
Shortest programme duration in min.	36
Maximum final rinse temperature in °C	82
Cleaning performance, place settings/cycle	13
Service life in wash cycles	12,500
Controls	
Control system	Electronic controls
Programme selection	Program Selector Buttons
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Filter indicator light	•
Selectable display languages	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	1.90
Total connected load in kW	2.10
Fuse rating in A	13
Length of mains connection cable in m	1.70
Provided with plug	•

For further information see the following pages

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.

Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	6.1
Total connected load in kW	6.30
Fuse rating in A	32
Water connection/drainage	
Cold or hot water [number]	1
Required flow pressure in bar	0,30-10,00
Drain pump [DN]	22
Maximum delivery head for drain pump in cm	100
Integrated water softener	•
Maximum water hardness in mmol/l	6.50
Water protection system	Waterproof system
Length of water inlet hose in cm	150
Length of water drain hose in cm	150
Dimensions and weight	
External dimensions, net height in mm	845
External dimensions with lid, height in mm	845
External dimensions, net width in mm	598
External dimensions, net depth in mm	570
External dimensions, gross height in mm	960
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	700
Usable space in wash cabinet, height in mm	540
Usable space in wash cabinet, width in mm	510
Usable space in wash cabinet, depth of upper basket in mm	450
Usable space in wash cabinet, depth of lower basket in mm	450
In-feed height above floor in mm	210
Net weight in kg	60
Gross weight in kg	67
Maximum floor loading in N	1,000
Emissions data	
Sound power (LwA) in dB(A) re 1 pW	46.0
Programmes	
Universal	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Plastics	•
Energy save/Eco	•
Intensive	•

For further information see the following pages

PFD 101

Free-standing dishwasher

For large amounts of crockery in households, office tea rooms and utility areas.

Basket design	
ExtraComfort baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	2
FlexCare cup rack [number]	1
Cutlery basket	•
Height-adjustable upper basket	•
Features	
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
AutoOpen assisted drying	•
AutoClose	•
EcoFeedback	•
Brilliant GlassCare	•
Safety lock	•
Adjustable final rinse temperature	•
Optical interface	•
SmartStart	•
FlexiTimer with EcoStart	•
Efficiency and sustainability	
Load size of the ECO programme in place settings	13
Energy efficiency class (A–G)	E
Energy consumption of the ECO programme per 100 cycles in kWh	93
Water consumption of the ECO programme per cycle in l	12
Airborne noise emission rating (A–D)	C
Airborne noise emission in dB(A) re 1 pW	46
Programme running time of the ECO programme in min	250
Connection options	
External dispensing module for liquid detergent	•
Test certificate	
CE	•
Complies with Machinery Directive 2006/42/EC	•
VDE	•
EMC radio suppressed	•
EN 1717	•

The Miele Company Limited
Fairacres
Marcham Road
Abingdon
OX14 1TW

Sales: 0845 365 6636
Customer Service: 0845 365 6608
miele-professional@miele.co.uk
www.miele.co.uk/professional
Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment.
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.