Miele Benchmark PDR528 Tumble Dryer

PDR 528 ROP [EL]

Professional vented dryer, electric heating
with M Select ROP residual moisture control for perfect drying results.

- Drum volume 500l , load size 20.0 – 28.0 kg
- Unique, gentle fabric care – honeycomb drum
- Greatest energy efficiency thanks to Air Recycling
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516409243 / Article number : 52528001EU / Material number: 11718340

Construction type and version	
Construction type	Front loader
Range	Performance
Front	Iron grey
Maximum load size in kg	28.0
Load size with a load ratio of 1:25	20.0
Load size with a load ratio of 1:18	28.0
Drum volume in l	500
Drying system	Vented
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundries	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in l/hour	25.8
Specific energy consumption in kWh/kg	0.49
Programme duration in min.	25
Tested operating hours	20,000
Controls	
Control system	M Select
Programmability	Setting of defined parameters
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Control panel with easy-to-understand symbols	•

PDR 528 ROP [EL]

Professional vented dryer, electric heating
with M Select ROP residual moisture control for perfect drying results.

Standard electrical connection	
Heating type	Electrical
Electrical connection	3N AC 400V 50/60HZ
Electric heater rating in kW	27.00
Total connected load in kW	28.20
Fuse rating in A	50
Possible voltage variant 1	
Electrical connection	3N AC 400V 60HZ
Electric heater rating in kW	27.0
Total connected load in kW	28.20
Fuse rating in A	50
Dimensions and weight	
External dimensions, net height in mm	1,640
External dimensions, net width in mm	1,206
External dimensions, net depth in mm	1,019
External dimensions, gross height in mm	1,766
External dimensions, gross width in mm	1,390
External dimensions, gross depth in mm	1,108
Net weight in kg	243
Gross weight in kg	258
Maximum floor loading in N	2799
Emissions data	
Heat dissipation into the room in MJ/h	3.30
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
Air Recycling	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Connector Box	•
LAN/WiFi module (optional)	•

PDR 528 ROP [EL]

Professional vented dryer, electric heating
with M Select ROP residual moisture control for perfect drying results.

Standards, test certificates and symbols	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

PDR 528 ROP [G]

Professional vented dryer, gas heating
with M Select ROP residual moisture control for perfect drying results.

- Drum volume 500l , load size 20.0 – 28.0 kg
- Unique, gentle fabric care – honeycomb drum
- Greatest energy efficiency thanks to Air Recycling
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516409373 / Article number : 52528003EU / Material number: 11718600

Construction type and version	
Construction type	Front loader
Range	Performance
Front	Iron grey
Maximum load size in kg	28.0
Load size with a load ratio of 1:25	20.0
Load size with a load ratio of 1:18	28.0
Drum volume in l	500
Drying system	Vented
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in l/hour	28.3
Specific energy consumption in kWh/kg	0.55
Tested operating hours	20,000
Controls	
Control system	M Select
Programmability	Setting of defined parameters
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Control panel with easy-to-understand symbols	•

PDR 528 ROP [G]

Professional vented dryer, gas heating
with M Select ROP residual moisture control for perfect drying results.

Standard electrical connection	
Heating type	Gas
Electrical connection	1N AC 230V 50HZ
Gas heater rating in kW	30.00
Total connected load in kW	1.20
Fuse rating in A	10
Possible voltage variant 1	
Electrical connection	3N AC 400V 60HZ
Electric heater rating in kW	27.0
Total connected load in kW	28.20
Fuse rating in A	50
Dimensions and weight	
External dimensions, net height in mm	1,640
External dimensions, net width in mm	1,206
External dimensions, net depth in mm	1,019
External dimensions, gross height in mm	1,766
External dimensions, gross width in mm	1,390
External dimensions, gross depth in mm	1,108
Net weight in kg	246
Gross weight in kg	261
Maximum floor loading in N	2828
Emissions data	
Heat dissipation into the room in MJ/h	3.30
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
Air Recycling	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Connector Box	•
LAN/WiFi module (optional)	•

PDR 528 ROP [G]

Professional vented dryer, gas heating
with M Select ROP residual moisture control for perfect drying results.

Standards, test certificates and symbols	
CE	•
VDE	•
Splash-proof safety rating IPX4	•
DVGW gas	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited
Fairacres
Marcham Road
Abingdon
OX14 1TW

Sales: 0845 365 6636
Customer Service: 0845 365 6608
miele-professional@miele.co.uk
www.miele.co.uk/professional
Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment.
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.