

Miele

JTM Service - Miele PFD 401 Speed Plus Dishwasher



PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



- Max. cleaning performance*: 380 plates/h or 24baskets/h
- Versatile processing of two wire or plastic baskets per cycle
- Excellent user convenience with touch display – M Touch Basic
- Always the right programme - item-specific solutions
- First-class results thanks to freshwater wash system

EAN: 4002516577003 / Article number: 61040115GB / Material number: 12066230

Construction type and design

Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Speedplus
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised

Application

Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for offices	•
Suitable for small businesses	•
Suitable for fast food restaurants	•
Suitable for sports clubs	•

Performance data

Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	6
Maximum final rinse temperature in °C	70
Cleaning performance, plates/h	380
Cleaning performance, baskets/h	24
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000

Miele MOVE

Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	•
Self-help function	•
Installation of remote updates and software updates	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Controls	
Control system	M Touch Basic
Max. delay start in h	24
Time left display	•
Programmes [number]	11
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	8.5
Total connected load in kW	8.9
Fuse rating in A	15-16
Length of mains connection cable in m	1.9
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	3
Total connected load in kW	3.4
Fuse rating in A	15-16
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	0.4-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Length of water inlet hose in cm	170
Length of water drain hose in cm	150

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Dimensions and weight	
External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	536
Usable space in wash cabinet, depth of upper basket	474
Usable space in wash cabinet, depth of lower basket in mm	516
In-feed height above floor in mm	216
Required niche width in mm	600
Net weight [kg]	75
Gross weight in kg	85
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	47 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	59
Heat dissipation into the room in MJ/h	1.44
Programmes	
Universal	•
Super short	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Beer glasses	•
Cutlery	•
Plastics	•
Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Features	
Drying	without
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
Perfect GlassCare	•
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, certs, symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



- Max. cleaning performance*: 456 plates/h or 20baskets/h
- Versatile processing of two wire or plastic baskets per cycle
- Excellent user convenience with touch display – M Touch Basic
- Always the right programme - item-specific solutions
- First-class results thanks to freshwater wash system

EAN: 4002516576914 / Article number: 61040110GB / Material number: 12066120

Construction type and design

Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Speedplus
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised

Application

Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for offices	•
Suitable for small businesses	•
Suitable for fast food restaurants	•
Suitable for sports clubs	•

Performance data

Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	5
Maximum final rinse temperature in °C	70
Cleaning performance, plates/h	456
Cleaning performance, baskets/h	20
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000

Miele MOVE

Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	•
Self-help function	•
Installation of remote updates and software updates	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Controls	
Control system	M Touch Basic
Max. delay start in h	24
Time left display	•
Programmes [number]	11
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	5.5
Total connected load in kW	5.9
Fuse rating in A	30-32
Length of mains connection cable in m	1.9
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	2.5
Total connected load in kW	2.9
Fuse rating in A	13
Possible voltage variant 2	
Electrical connection	AC 230V 50HZ
Heater rating in kW	3
Total connected load in kW	3.4
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	0.4-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Length of water inlet hose in cm	170
Length of water drain hose in cm	150

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Dimensions and weight	
External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	536
Usable space in wash cabinet, depth of upper basket	474
Usable space in wash cabinet, depth of lower basket in mm	516
In-feed height above floor in mm	216
Required niche width in mm	600
Net weight [kg]	75
Gross weight in kg	85
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	47 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	59
Heat dissipation into the room in MJ/h	1.44
Programmes	
Universal	•
Super short	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Beer glasses	•
Cutlery	•
Plastics	•
Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Features	
Drying	without
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
Perfect GlassCare	•
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, certs, symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



- Max. cleaning performance*: 380 plates/h or 20baskets/h
- Versatile processing of two wire or plastic baskets per cycle
- Excellent user convenience with touch display – M Touch Basic
- Always the right programme - item-specific solutions
- First-class results thanks to freshwater wash system

EAN: 4002516576938 / Article number: 61040101GB / Material number: 12066140

Construction type and design

Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Speedplus
Wash system	Fresh water front loader
Number of levels	2
Front	Lotus white
Lid	Lotus White
Side panels	Lotus White
Rear panel	Galvanised

Application

Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for offices	•
Suitable for small businesses	•
Suitable for fast food restaurants	•
Suitable for sports clubs	•

Performance data

Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	6
Maximum final rinse temperature in °C	70
Cleaning performance, plates/h	380
Cleaning performance, baskets/h	20
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000

Miele MOVE

Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	•
Self-help function	•
Installation of remote updates and software updates	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Controls	
Control system	M Touch Basic
Max. delay start in h	24
Time left display	•
Programmes [number]	11
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	5.5
Total connected load in kW	5.9
Fuse rating in A	30-32
Length of mains connection cable in m	1.9
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	2.5
Total connected load in kW	2.9
Fuse rating in A	13
Possible voltage variant 2	
Electrical connection	AC 230V 50HZ
Heater rating in kW	3
Total connected load in kW	3.4
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	0.4-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Length of water inlet hose in cm	170
Length of water drain hose in cm	150

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Dimensions and weight	
External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	536
Usable space in wash cabinet, depth of upper basket	474
Usable space in wash cabinet, depth of lower basket in mm	516
In-feed height above floor in mm	216
Required niche width in mm	600
Net weight [kg]	75
Gross weight in kg	85
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	47 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	59
Heat dissipation into the room in MJ/h	1.44
Programmes	
Universal	•
Super short	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Beer glasses	•
Cutlery	•
Plastics	•
Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•

PFD 401 [WB SpeedPlus]

Freestanding fresh water dishwasher

With baskets for hotels, restaurants and catering companies.



Features	
Drying	without
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
Perfect GlassCare	•
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, certs, symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•

The Miele logo is displayed in white, bold, sans-serif font against a dark red rectangular background.

Miele

Miele Ireland Ltd.

2024 Bianconi Avenue
CityWest Business Campus
Dublin 24

Tel: 01 4499251 / 01 4610710

Service: 1890 252 609*

E-Mail: professionalservice@miele.ie

*Lo-call number. Calls charged at local rate