

Miele

JTM Service - Miele PFD 404 Hygiene Dishwasher



PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



- Max. cleaning performance*: 380 plates/h or 20baskets/h
- First-class results thanks to freshwater wash system
- Extremely hygienic results –final rinse temperature of 85 °C
- Safe and easy operation - automatic door opening
- Maximum convenience with M Touch Flex full-touch colour display

EAN: 4002516576969 / Article number: 61040410GB / Material number: 12066190

Construction type and design	
Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Hygiene
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised
Application	
Suitable for retirement and care homes	•
Suitable for hospitals	•
Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for child care facilities	•
Suitable for fast food restaurants	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	6
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	380
Cleaning performance, baskets/h	20
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000
Miele MOVE	
Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	•
Self-help function	•
Installation of remote updates and software updates	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Controls	
Control system	M Touch Flex
Max. delay start in h	24
Time left display	•
Programmes [number]	12
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	5.5
Total connected load in kW	5.9
Fuse rating in A	30-32
Length of mains connection cable in m	1.9
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	2.5
Total connected load in kW	2.9
Fuse rating in A	13
Possible voltage variant 2	
Electrical connection	AC 230V 50HZ
Heater rating in kW	3
Total connected load in kW	3.4
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	0.4-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Length of water inlet hose in cm	170
Length of water drain hose in cm	150

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Dimensions and weight	
External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	536
Usable space in wash cabinet, depth of upper basket	474
Usable space in wash cabinet, depth of lower basket in mm	516
In-feed height above floor in mm	216
Required niche width in mm	600
Net weight [kg]	78
Gross weight in kg	88
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57
Heat dissipation into the room in MJ/h	1.44
Programmes	
Universal	•
Super short	•
Short	•
Hygiene	•
Hygiene plus	•
Cold/Pre-wash	•
Glasses	•
Beer glasses	•
Cutlery	•
Plastics	•
Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Features	
Drying	AutoOpen assisted drying
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
AutoClose	•
Perfect GlassCare	•
Aerosol steam condenser	•
Door lock, protected by code	•
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, certs, symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



- Max. cleaning performance*: 380 plates/h or 20baskets/h
- First-class results thanks to freshwater wash system
- Extremely hygienic results –final rinse temperature of 85 °C
- Safe and easy operation - automatic door opening
- Maximum convenience with M Touch Flex full-touch colour display

EAN: 4002516576976 / Article number: 61040401GB / Material number: 12066200

Construction type and design	
Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Hygiene
Wash system	Fresh water front loader
Number of levels	2
Front	Lotus white
Lid	Lotus White
Side panels	Lotus White
Rear panel	Galvanised
Application	
Suitable for retirement and care homes	•
Suitable for hospitals	•
Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for child care facilities	•
Suitable for fast food restaurants	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	6
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	380
Cleaning performance, baskets/h	20
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000
Miele MOVE	
Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	•
Self-help function	•
Installation of remote updates and software updates	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Controls	
Control system	M Touch Flex
Max. delay start in h	24
Time left display	•
Programmes [number]	12
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	5.5
Total connected load in kW	5.9
Fuse rating in A	30-32
Length of mains connection cable in m	1.9
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	2.5
Total connected load in kW	2.9
Fuse rating in A	13
Possible voltage variant 2	
Electrical connection	AC 230V 50HZ
Heater rating in kW	3
Total connected load in kW	3.4
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	0.4-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Length of water inlet hose in cm	170
Length of water drain hose in cm	150

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Dimensions and weight	
External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	536
Usable space in wash cabinet, depth of upper basket	474
Usable space in wash cabinet, depth of lower basket in mm	516
In-feed height above floor in mm	216
Required niche width in mm	600
Net weight [kg]	78
Gross weight in kg	88
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57
Heat dissipation into the room in MJ/h	1.44
Programmes	
Universal	•
Super short	•
Short	•
Hygiene	•
Hygiene plus	•
Cold/Pre-wash	•
Glasses	•
Beer glasses	•
Cutlery	•
Plastics	•
Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Features	
Drying	AutoOpen assisted drying
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stainless steel	•
In-door salt container	•
AutoClose	•
Perfect GlassCare	•
Aerosol steam condenser	•
Door lock, protected by code	•
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, certs, symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



- Max. cleaning performance*: 456 plates/h or 24baskets/h
- First-class results thanks to freshwater wash system
- Extremely hygienic results –final rinse temperature of 85 °C
- Safe and easy operation - automatic door opening
- Maximum convenience with M Touch Flex full-touch colour display

EAN: 4002516577010 / Article number: 61040415GB / Material number: 12066240

Construction type and design	
Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Hygiene
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised
Application	
Suitable for retirement and care homes	•
Suitable for hospitals	•
Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for child care facilities	•
Suitable for fast food restaurants	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	390
Shortest programme duration in min.	5
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	456
Cleaning performance, baskets/h	24
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000
Miele MOVE	
Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	•
Self-help function	•
Installation of remote updates and software updates	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Controls	
Control system	M Touch Flex
Max. delay start in h	24
Time left display	•
Programmes [number]	12
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	8.5
Total connected load in kW	8.9
Fuse rating in A	15-16
Length of mains connection cable in m	1.9
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	3
Total connected load in kW	3.4
Fuse rating in A	15-16
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	0.4-10
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	10.7
Water protection system	Waterproof system
Water consumption per wash cycle in l	8
Length of water inlet hose in cm	170
Length of water drain hose in cm	150

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Dimensions and weight	
External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	536
Usable space in wash cabinet, depth of upper basket	474
Usable space in wash cabinet, depth of lower basket in mm	516
In-feed height above floor in mm	216
Required niche width in mm	600
Net weight [kg]	78
Gross weight in kg	88
Maximum floor loading in N	1200
Emissions data	
Emissions – sound pressure at workplace	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57
Heat dissipation into the room in MJ/h	1.44
Programmes	
Universal	•
Super short	•
Short	•
Hygiene	•
Hygiene plus	•
Cold/Pre-wash	•
Glasses	•
Beer glasses	•
Cutlery	•
Plastics	•
Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•

PFD 404 [WB Hygiene]

Freestanding fresh water dishwasher

With baskets, for all locations with high hygiene requirements.



Features	
Drying	AutoOpen assisted drying
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
AutoClose	•
Perfect GlassCare	•
Aerosol steam condenser	•
Door lock, protected by code	•
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, certs, symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•

Miele Ireland Ltd.

2024 Bianconi Avenue
CityWest Business Campus
Dublin 24

Tel: 01 4499251 / 01 4610710

Service: 1890 252 609*

E-Mail: professionalservice@miele.ie

*Lo-call number. Calls charged at local rate