JTM Service - Miele Professional PWM 909 Washing Machine





PWM 909 [EL DP DD]

Professional washing machine, electric heating, drain pump and detergent drawer, M Touch Pro Plus – freely programmable.



- Drum volume 80 I, load size 9 kg
- Ideal operation thanks to colour touch display – M Touch Pro Plus
- Perfect spinning results residual moisture 44 %*, g-factor518
- Connected for the future using LAN and WiFi

EAN: 4002516520009 / Article number: 51909003GB / Material number: 11961060

Construction type and design	
Construction type	Front loader
Range	Performance Plus
Front	Iron grey
Control panel colour	Stainless steel
Load ratio	1:9
Load in kg	9
Drum volume in I	80
Door opening [Ø] in mm	370
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Maintenance-free synchronous motor	•
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for facility management	•
Suitable for launderettes	•
Suitable for residential homes and apartments	
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•

PWM 909 [EL DP DD]



Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in	
l/kg	6.3
Specific energy consumption for cold water connection in kWh/kg	0.13
Specific water consumption for hot water connection in I/kg	6.6
Specific energy consumption for hot water connection in kWh/kg	0.03
Water consumption with cold water connection in I	56.2
Energy consumption with cold water connection in kW	1.2
Programme duration in minutes with cold water connection	49
Water consumption with hot water connection in I	59.3
Energy consumption with hot water connection in kW	0.23
Programme duration in minutes with cold water and hot water connection	45
Water consumption in ECO programme with cold water connection in I	49.7
Energy consumption in ECO programme with cold water	0.82
Programme duration in minutes with cold water connection in ECO programme	34
Water consumption in ECO programme with hot water connection in I	52
Energy consumption in ECO programme with hot water	0.14
Programme duration in minutes with cold water and hot water connection in ECO programme	32
Programme running time in minutes for Mops standard	0.22
60 °C programme with hot water connection	0.23
Residual moisture with cold rinse in %	47
Residual moisture with hot rinse in %	44
Spin speed in rpm	1300
g factor	518
Tested operating hours	30000
Controls	
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Dispensing	
Detergent drawer	3 compartments
Flexible dispensing adapter (optional)	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•

PWM 909 [EL DP DD]



Standard electrical connection	-
Heating type	Electric
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	7.95
Total connected load in kW	8.2
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Grey water (optional) [number]	1 x 1/2" w/ 3/4" union
Drain pump	DN 22
Dimensions and weight	
External dimensions, height in mm	1020
External dimensions, width in mm	700
External dimensions, depth in mm	718
External dimensions, gross height in mm	1214
External dimensions, gross width in mm	750
External dimensions, gross depth in mm	817
Net weight in kg	140
Gross weight in kg	152
Maximum floor loading in N	2421
Emissions data	
Emission sound pressure level in the workplace	65 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	2.3
Features	
Patented pre-spin	<u> </u>
Cloth reprocessing	<u>•</u>
3-dimensional imbalance monitoring	<u>•</u>
Disinfection rinse	<u>•</u>
EcoSpeed	<u> </u>
Temperature monitoring	<u> </u>
Special heater element	<u> </u>
Automatic load control+	•
Flow meter	•
Add laundry	•
Programme selection via colour frame	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95

PWM 909 [EL DP DD]



Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN	•
WiFi	•
Connector Box	•
Capacities	
Respirator masks [number]	13
Helmets [number]	2
Overalls [number]	1
Over jackets [number]	2
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Cloths, 22 g [number]	204
Cotton mops, 40 cm / 190 g [number]	42
Cotton mops, 50 cm / 220 g [number]	33
Microfibre mops, 40 cm / 120 g [number]	66
Microfibre mops, 50 cm / 170 g [number]	43
Mops, office, 100 g [quantity]	55
Mops, stairway, 150 g [quantity]	35
Summer horse blankets [number]	2
Standards, certs, symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WRAS	•
UKCA	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

Miele

PWM 909 [EL DV DD]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus – freely programmable.



- Drum volume 80 I, load size 9 kg
- Ideal operation thanks to colour touch display M Touch Pro Plus
- Perfect spinning results residual moisture 44 %*, g-factor518
- Connected for the future using LAN and WiFi

EAN: 4002516488187 / Article number: 51909001GB / Material number: 11923480

Construction type and design	
Construction type	Front loader
Range	Performance Plus
Front	Iron grey
Control panel colour	Stainless steel
Load ratio	1:9
Load in kg	9
Drum volume in I	80
Door opening [Ø] in mm	370
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Maintenance-free synchronous motor	•
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	<u> </u>
Suitable for facility management	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•

PWM 909 [EL DV DD]



Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in	- -
I/kg	6.3
Specific energy consumption for cold water connection in	0.13
kWh/kg Specific water consumption for hot water connection in	
l/kg	6.6
Specific energy consumption for hot water connection in kWh/kg	0.03
Water consumption with cold water connection in I	56.2
Energy consumption with cold water connection in kW	1.2
Programme duration in minutes with cold water connection	49
Water consumption with hot water connection in I	59.3
Energy consumption with hot water connection in kW	0.23
Programme duration in minutes with cold water and hot	
water connection	45
Water consumption in ECO programme with cold water connection in I	49.7
Energy consumption in ECO programme with cold water	0.82
Programme duration in minutes with cold water	34
connection in ECO programme Water consumption in ECO programme with hot water	
connection in I	52
Energy consumption in ECO programme with hot water	0.14
Programme duration in minutes with cold water and hot	32
water connection in ECO programme	
Programme running time in minutes for Mops standard 60 °C programme with hot water connection	0.23
Residual moisture with cold rinse in %	47
Residual moisture with hot rinse in %	44
Spin speed in rpm	1300
g factor	518
Tested operating hours	30000
Controls	
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Dispensing	
Detergent drawer	3 compartments
Flexible dispensing adapter (optional)	•
Maximum number of connections for liquid dispenser	
pumps [number]	6
Empty sensor	•

PWM 909 [EL DV DD]



31 0	
Standard electrical connection	
Heating type	Electric
Electrical connection	3N AC 400V 50/60HZ
Heater rating in kW	7.95
Total connected load in kW	8.2
Fuse rating in A	16
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Grey water (optional) [number]	1 x 1/2" w/ 3/4" union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	1020
External dimensions, width in mm	704
External dimensions, depth in mm	730
External dimensions, gross height in mm	1214
External dimensions, gross width in mm	750
External dimensions, gross depth in mm	817
Net weight in kg	140
Gross weight in kg	152
Maximum floor loading in N	2421
Emissions data	
Emission sound pressure level in the workplace	65 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	2.3
Features	
Patented pre-spin	<u>•</u>
Cloth reprocessing	•
3-dimensional imbalance monitoring	
Disinfection rinse	<u>•</u>
EcoSpeed	
Temperature monitoring	<u> </u>
Special heater element	<u> </u>
Automatic load control+	<u> </u>
Flow meter	•
Add laundry	
Programme selection via colour frame	<u> </u>
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95

PWM 909 [EL DV DD]



Connection antique	
Connection options Downerst existent (antional)	
Payment system (optional)	
Optical interface for service access	<u>•</u>
Peak load cut-out/energy management (optional)	<u> </u>
LAN	<u> </u>
WiFi	<u> </u>
Connector Box	<u>•</u>
Capacities	
Respirator masks [number]	13
Helmets [number]	2
Overalls [number]	1
Over jackets [number]	2
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Cloths, 22 g [number]	204
Cotton mops, 40 cm / 190 g [number]	42
Cotton mops, 50 cm / 220 g [number]	33
Microfibre mops, 40 cm / 120 g [number]	_66
Microfibre mops, 50 cm / 170 g [number]	43
Mops, office, 100 g [quantity]	55
Mops, stairway, 150 g [quantity]	35
Summer horse blankets [number]	2
Standards, certs, symbols	
CE	<u> </u>
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WRAS	•
UKCA	<u> </u>
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

Miele

PWM 909 [EL DV DD]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus – freely programmable.



- Drum volume 80 I, load size 9 kg
- Ideal operation thanks to colour touch display M Touch Pro Plus
- Perfect spinning results residual moisture 44 %*, g-factor518
- Connected for the future using LAN and WiFi

EAN: 4002516520344 / Article number: 51909021GB / Material number: 11961100

Construction type and design	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:9
Load in kg	9
Drum volume in I	80
Door opening [Ø] in mm	370
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Maintenance-free synchronous motor	•
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for facility management	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•

Miele

PWM 909 [EL DV DD]



Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in	6.3
l/kg	-
Specific energy consumption for cold water connection in	0.13
kWh/kg Specific water consumption for hot water connection in	
l/kg	6.6
Specific energy consumption for hot water connection in kWh/kg	0.03
Water consumption with cold water connection in I	56.2
Energy consumption with cold water connection in kW	1.2
Programme duration in minutes with cold water	
connection	
Water consumption with hot water connection in I	59.3
Energy consumption with hot water connection in kW	0.23
Programme duration in minutes with cold water and hot water connection	45
Water consumption in ECO programme with cold water	49.7
connection in I	
Energy consumption in ECO programme with cold water	
Programme duration in minutes with cold water connection in ECO programme	34
Water consumption in ECO programme with hot water	
connection in I	52
Energy consumption in ECO programme with hot water	0.14
Programme duration in minutes with cold water and hot	32
water connection in ECO programme	
Residual moisture with cold rinse in %	47
Residual moisture with hot rinse in %	44
Spin speed in rpm	1300
g factor	518
Tested operating hours	30000
Controls	
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Dispensing	
Detergent drawer	3 compartments
Flexible dispensing adapter (optional)	•
Maximum number of connections for liquid dispenser	
pumps [number]	6
Empty sensor	•

PWM 909 [EL DV DD]



31 0	
Standard electrical connection	
Heating type	Electric
Electrical connection	1N AC 230V 50/60HZ
Heater rating in kW	5.3
Total connected load in kW	5.5
Fuse rating in A	25
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Grey water (optional) [number]	1 x 1/2" w/ 3/4" union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	1020
External dimensions, width in mm	700
External dimensions, depth in mm	730
External dimensions, gross height in mm	1214
External dimensions, gross width in mm	750
External dimensions, gross depth in mm	817
Net weight in kg	140
Gross weight in kg	152
Maximum floor loading in N	2421
Emissions data	
Emission sound pressure level in the workplace	65 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	2.3
Features	
Patented pre-spin	<u>•</u>
Cloth reprocessing	•
3-dimensional imbalance monitoring	
Disinfection rinse	<u>•</u>
EcoSpeed	<u>•</u>
Temperature monitoring	<u> </u>
Special heater element	<u> </u>
Automatic load control+	<u> </u>
Flow meter	•
Add laundry	•
Programme selection via colour frame	<u> </u>
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95

PWM 909 [EL DV DD]



Connection antique	
Connection options Downerst existent (antional)	
Payment system (optional)	
Optical interface for service access	<u>•</u>
Peak load cut-out/energy management (optional)	<u> </u>
LAN	<u> </u>
WiFi	<u> </u>
Connector Box	<u>•</u>
Capacities	
Respirator masks [number]	13
Helmets [number]	2
Overalls [number]	1
Over jackets [number]	2
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Cloths, 22 g [number]	204
Cotton mops, 40 cm / 190 g [number]	42
Cotton mops, 50 cm / 220 g [number]	33
Microfibre mops, 40 cm / 120 g [number]	_66
Microfibre mops, 50 cm / 170 g [number]	43
Mops, office, 100 g [quantity]	55
Mops, stairway, 150 g [quantity]	35
Summer horse blankets [number]	2
Standards, certs, symbols	
CE	<u> </u>
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WRAS	•
UKCA	<u> </u>
WEEE	•
Complies with Machinery Directive 2006/42/EC	•



The Miele Company Limited Fairacres Marcham Road Abingdon OX14 1TW

Sales: 0845 365 6636

Customer Service: 0845 365 6608 miele-professional@miele.co.uk www.miele.co.uk/professional

Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment. For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.