

Miele

JTM Service Ltd - Miele Professional PDR 507 Vented - Brochure



PDR 507 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 7 kg in 46 min.



- Drum volume 130 l, load size 7 kg
- Tested for intensive use – unparalleled Miele quality
- Language-neutral fascia panel with rotary control – M Select
- Precision drying of all fabrics – PerfectDry

C

EAN: 4002516127116 / Article number: 52507354GB / Material number: 11104040

Construction type and version	
Construction type	Front-loader, stackable
Range	Performance
Front	Lotus white
Fascia color	Stainless steel
Load in kg	7
Drum volume in l	130
Drying system	Exhaust air
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for domestic use	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in l/hour	4.4
Specific energy consumption in kWh/kg	0.5
Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kW	0.5
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 48 % in kW	0.42
Programme duration in min.	46
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	46
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in minutes	41

PDR 507 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 7 kg in 46 min.



Control system	
Control system	M Select
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Control panel with easy-to-understand symbols	•
Language can be selected easily at any time	•
Standard electrical connection	
Heating type	Electric
Electrical connection	220-230V~ 50/60HZ
Electric heater rating in kW	4.78-5.22
Total connected load in kW	5.03-5.47
Fuse rating in A	25
Possible voltage variant 1	
Electrical connection	220-230V~ 50HZ
Heater rating in kW	0
Total connected load in kW	5.03-5.47
Fuse rating in A	25
Possible voltage variant 2	
Electrical connection	3~ 230V 50/60HZ
Heater rating in kW	6.14
Total connected load in kW	6.4
Fuse rating in A	16
Dimensions and weight of dryer	
External dimensions, height in mm	850
External dimensions, width in mm	596
External dimensions, depth in mm	717
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	820
Net weight in kg	49
Gross weight in kg	55
Maximum floor load in N/m ²	920
Emissions data	
Emission sound pressure level in the workplace	<lt>70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	0.76

PDR 507 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 7 kg in 46 min.



Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Communication slot	•
Drying basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
Efficiency and sustainability	
Energy efficiency class	C
Annual energy consumption in kWh	543
Noise in dB(a) in the Cottons Normal dry standard programme with a full load	66
Duration in minutes in the standard programme	58
How it works	Vented
Load in kg	7
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
WiFiConn@ct	•
Standards, test certificates and symbols	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

PDR 507 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 7 kg in 77 min.



- Drum volume 130 l, load size 7 kg
- Tested for intensive use – unparalleled Miele quality
- Language-neutral fascia panel with rotary control – M Select
- Precision drying of all fabrics – PerfectDry

C

EAN: 4002516127000 / Article number: 52507353GB / Material number: 11103940

Construction type and version	
Construction type	Front-loader, stackable
Range	Performance
Front	Lotus white
Fascia color	Stainless steel
Load in kg	7
Drum volume in l	130
Drying system	Exhaust air
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for domestic use	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in l/hour	2.6
Specific energy consumption in kWh/kg	0.49
Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kW	0.49
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture at 48 % in kW	0.41
Programme duration in min.	77
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	77
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in minutes	66

PDR 507 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 7 kg in 77 min.



Control system	
Control system	M Select
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Control panel with easy-to-understand symbols	•
Language can be selected easily at any time	•
Standard electrical connection	
Heating type	Electric
Electrical connection	220-230V~ 50/60HZ
Electric heater rating in kW	2.52-2.76
Total connected load in kW	2.76-2.99
Fuse rating in A	13
Possible voltage variant 1	
Heater rating in kW	2.76
Fuse rating in A	13-13
Possible voltage variant 2	
Heater rating in kW	6.14
Total connected load in kW	6.4
Fuse rating in A	16-16
Dimensions and weight of dryer	
External dimensions, height in mm	850
External dimensions, width in mm	596
External dimensions, depth in mm	717
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	820
Net weight in kg	49
Gross weight in kg	55
Maximum floor load in N/m ²	920
Emissions data	
Emission sound pressure level in the workplace	<lt/>70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	0.76

PDR 507 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 7 kg in 77 min.



Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Communication slot	•
Drying basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
Efficiency and sustainability	
Energy efficiency class	C
Annual energy consumption in kWh	524
Noise in dB(a) in the Cottons Normal dry standard programme with a full load	66
Duration in minutes in the standard programme	95
How it works	Vented
Load in kg	7
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
WiFiConn@ct	•
Standards, test certificates and symbols	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited
Fairacres
Marcham Road
Abingdon
OX14 1TW

Sales: 0845 365 6636
Customer Service: 0845 365 6608
miele-professional@miele.co.uk
www.miele.co.uk/professional
Twitter: @MieleProf

**Professional laundry, dishwashing,
disinfection and sterilisation equipment.**
For many years Miele Professional has been
at the forefront of manufacturing commercial
laundry, dishwashing, disinfecting and
sterilisation equipment, bringing you a
comprehensive selection of machines for
a wide range of applications. Whatever the
business sector our commercial range has it
covered.