Míele

JTM Service - Miele PRI 210 Ironer



Miele

PRI 210 [EL STW AB]

Rotary ironer, electrically heated

With the latest controls and flexible working height.



- Performance 30 kg/h^{*}, roller diameter 210 mm, working width 1000 mm
- Ideal ergonomics height-adjustable and optional plinth
- State-of-the-art controls Touch display
- Selection of the most important settings favourite programmes
- Perfect rotary ironing performance flexibly positioned heater plate

EAN: 4002516422242 / Article number: 53210004EU / Material number: 11741260

EAN: 4002516422242 / Article number: 53210004EU / Ma Construction type and version		
·	Laundry infeed and outfeed	
Construction type	at the front	
Can be set up against a wall	<u>•</u>	
Range	Professional	
Outer casing	Iron grey	
Roller diameter in mm	210	
Working width in mm	1000	
Heater plate material	Aluminium	
Padding	Supple steel wool	
Ironer cover	ARAMID needle-felt cloth	
Application		
Suitable for the hotel and catering industry	<u> </u>	
Suitable for retirement and care homes	<u> </u>	
Suitable for launderettes	•	
Suitable for residential homes and apartments	•	
Suitable for hospitals	•	
Suitable for offshore use	•	
Suitable for marine use	•	
Suitable for camp sites	•	
Suitable for domestic use	•	
Performance data		
Max. ironing performance at 15 % residual moisture in kg/h	30	
Tested operating hours	20000	
Control system		
Control system	Touch display	
Programme setting	Setting of defined programme parameters	
Minimum ironing speed, controlled in m/min	1.5	
Maximum ironing speed, controlled in m/min	4	
Adjustable temperature	Infinitely variable	
Standard electrical connection		
Heating type	Electric	
Electrical connection	3N AC 400V 50-60HZ	
Electric heater rating in kW	4.5	
Total connected load in kW	5	
Fuse rating in A	16	



Rotary ironer, electrically heated

With the latest controls and flexible working height.



Dimensions and weight	
External dimensions, height in mm	1032
External dimensions, width in mm	1579
External dimensions, depth in mm	476
External dimensions, gross height in mm	1374
External dimensions, gross width in mm	1763
External dimensions, gross depth in mm	660
Net weight in kg	122
Gross weight in kg	136
Maximum floor load in N/m ²	1220
Emissions data	
Emission sound pressure level in the workplace	<lt></lt> 70 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	4.5
Features	
Automatic finger guard	•
FlexControl footswitch	
Airing bar	•
Feed-in board	•
Pick-off bands	•
Laundry box (optional)	•
Laundry return feed	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Plinth (optional)	•
Option of ironing when seated	•
APRI 319 care set for the heater plate included in the	•
scope of delivery	
Machine-independent accessories	•
Connection options Payment system (optional)	•
Peak-load negotiation / energy management	•



Rotary ironer, electrically heated

With the latest controls and flexible working height.



Standards, test certificates and symbols	
VDE	•
CE	•
EAC	•
WEEE	•
VDE-EMC	•
RCM	•
Splash-proof IPX0	•
UKCA	•
O 1 1 - Marchine - Direction - 0000/40/E0	

Complies with Machinery Directive 2006/42/EC

Miele

PRI 210 [EL STW AB]

Rotary ironer, electrically heated

With the latest controls and flexible working height.



- Performance 23.5 kg/h*, roller diameter 210 mm, working width 1000 mm
- Ideal ergonomics height-adjustable and optional plinth
- State-of-the-art controls Touch display
- Selection of the most important settings - favourite programmes
- Perfect rotary ironing performance flexibly positioned heater plate

EAN: 4002516422266 / Article number: 53210005EU / M	aterial number: 11741270
Construction type and version	
Construction type	Laundry infeed and outfeed at the front
Can be set up against a wall	•
Range	Professional
Outer casing	Iron grey
Roller diameter in mm	210
Working width in mm	1000
Heater plate material	Aluminium
Padding	Supple steel wool
Ironer cover	ARAMID needle-felt cloth
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for hospitals	•
Suitable for offshore use	•
Suitable for marine use	•
Suitable for camp sites	•
Suitable for domestic use	•
Performance data	
Max. ironing performance at 15 % residual moisture in kg/h	23.5
Tested operating hours	20000
Control system	
Control system	Touch display
Programme setting	Setting of defined programme parameters
Minimum ironing speed, controlled in m/min	1.5
Maximum ironing speed, controlled in m/min	4
Adjustable temperature	Infinitely variable
Standard electrical connection	
Heating type	Electric
Electrical connection	AC 230V 50-60HZ
Electric heater rating in kW	3
Total connected load in kW	3.4
Fuse rating in A	16



Rotary ironer, electrically heated

With the latest controls and flexible working height.



Dimensions and weight	
External dimensions, height in mm	1032
External dimensions, width in mm	1579
External dimensions, depth in mm	476
External dimensions, gross height in mm	1374
External dimensions, gross width in mm	1763
External dimensions, gross depth in mm	660
Net weight in kg	122
Gross weight in kg	136
Maximum floor load in N/m²	1235
Emissions data	
Emission sound pressure level in the workplace	<lt></lt>70 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	3.3
Features	
Automatic finger guard	<u>•</u>
FlexControl footswitch	•
Airing bar	•
Feed-in board	•
Pick-off bands	•
Laundry box (optional)	•
Laundry return feed	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Plinth (optional)	•
Option of ironing when seated	•
APRI 319 care set for the heater plate included in the	•
scope of delivery	
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Peak-load negotiation / energy management	•



Rotary ironer, electrically heated

With the latest controls and flexible working height.



Standards, test certificates and symbols	
VDE	•
CE	•
EAC	•
WEEE	•
VDE-EMC	•
RCM	•
Splash-proof IPX0	•
UKCA	•
O 1 1 - Marchine - Direction - 0000/40/E0	

Complies with Machinery Directive 2006/42/EC



The Miele Company Limited Fairacres Marcham Road Abingdon OX14 1TW

Sales: 0845 365 6636

Customer Service: 0845 365 6608 miele-professional@miele.co.uk www.miele.co.uk/professional

Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment. For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.