

**Miele**

# JTM Service - Miele PRI 217 Ironer



## PRI 217 [EL STW FLT]

Rotary ironer, electrically heated

With the latest controls, steel wool padding and flexible laundry feed.



- Performance 60 kg/h\*, roller diameter 250 mm, working width 1660 mm
- Easily adjustable - flexible return feed
- Ideal ergonomics - height-adjustable and optional plinth
- State-of-the-art controls – Touch display
- Perfect rotary ironing performance - flexibly positioned heater plate

EAN: 4002516423034 / Article number: 53217010EU / Material number: 11744750

<b>Construction type and version</b>	
Construction type	Laundry infeed at the front, laundry outfeed at the back
Can be set up against a wall	•
Range	Professional
Outer casing	Iron grey
Roller diameter in mm	250
Working width in mm	1660
Heater plate material	Aluminium
Padding	Supple steel wool
Ironer cover	ARAMID needle-felt cloth
<b>Application</b>	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for commercial laundries	•
Suitable for hospitals	•
Suitable for offshore use	•
Suitable for marine use	•
Suitable for camp sites	•
<b>Performance data</b>	
Max. ironing performance at 25 % residual moisture in kg/h	60
Tested operating hours	20000
<b>Control system</b>	
Control system	Touch display
Programme setting	Setting of defined programme parameters
Minimum ironing speed, controlled in m/min	1.5
Maximum ironing speed, controlled in m/min	4.5
Adjustable temperature	Infinitely variable
<b>Standard electrical connection</b>	
Heating type	Electric
Electrical connection	3N AC 400V 50-60HZ
Electric heater rating in kW	11
Total connected load in kW	11.6
Fuse rating in A	25

PRI 217 [EL STW FLT]

Rotary ironer, electrically heated

With the latest controls, steel wool padding and flexible laundry feed.



<b>Dimensions and weight</b>	
External dimensions, height in mm	1110
External dimensions, width in mm	2238
External dimensions, depth in mm	650
External dimensions, gross height in mm	1414
External dimensions, gross width in mm	2400
External dimensions, gross depth in mm	860
Net weight in kg	189
Gross weight in kg	214
Maximum floor load in N/m <sup>2</sup>	1890
<b>Emissions data</b>	
Emission sound pressure level in the workplace	<lt/>70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	11
<b>Features</b>	
Automatic finger guard	•
FlexControl footswitch	•
Feed-in board	•
Pick-off bands	•
Laundry box	•
Flexible laundry feed	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Plinth (optional)	•
Option of ironing when seated	•
APRI 319 care set for the heater plate included in the scope of delivery	•
Machine-independent accessories	•
<b>Connection options</b>	
Payment system (optional)	•
Peak-load negotiation / energy management	•
<b>Standards, test certificates and symbols</b>	
VDE	•
CE	•
EAC	•
WEEE	•
VDE-EMC	•
RCM	•
Splash-proof IPX0	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited  
Fairacres  
Marcham Road  
Abingdon  
OX14 1TW

Sales: 0845 365 6636  
Customer Service: 0845 365 6608  
[miele-professional@miele.co.uk](mailto:miele-professional@miele.co.uk)  
[www.miele.co.uk/professional](http://www.miele.co.uk/professional)  
Twitter: @MieleProf

**Professional laundry, dishwashing, disinfection and sterilisation equipment.**  
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.