

Miele

Miele Professional PW 6321 & PW 6321 MF Washing Machine



PW 6321 [EL]

Washing machine, electrically heated

With individually programmable controls for the maximum in flexibility.



EAN: 4002516446903 / Article number: 51632105NER / Material number: 11813940

Construction type and version	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:10
Load in kg	32
Drum volume in l	320
Door opening [Ø] in mm	430
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•

- Drum volume 320 l, load size 32 kg
- Large programme variety - application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient - low water and energy consumption
- Perfect spinning results – residual moisture 47 %, g-factor 447

PW 6321 [EL]

Washing machine, electrically heated

With individually programmable controls for the maximum in flexibility.



Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in l/kg	9
Specific energy consumption for cold water connection in kWh/kg	0.25
Specific water consumption for hot water connection in l/kg	8.8
Specific energy consumption for hot water connection in kWh/kg	0.1
Water consumption with cold water connection in l	288
Energy consumption with cold water connection in kW	8
Programme duration in minutes with cold water connection	61
Water consumption with hot water connection in l	281.6
Energy consumption with hot water connection in kW	3.2
Programme duration in minutes with cold water and hot water connection	49
Water consumption in ECO programme with cold water connection in l	281.6
Energy consumption in ECO programme with cold water connection in ECO programme	6.2
Programme duration in minutes with cold water connection in ECO programme	47
Water consumption in ECO programme with hot water connection in l	284.8
Energy consumption in ECO programme with hot water connection in ECO programme	1.6
Programme duration in minutes with cold water and hot water connection in ECO programme	37
Residual moisture with cold rinse in %	50
Residual moisture with hot rinse in %	47
Spin speed in rpm	1000
g factor	447
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Dispensing	
Detergent drawer	3 compartments
Liquid dispensing module (optional)	•
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•

PW 6321 [EL]

Washing machine, electrically heated

With individually programmable controls for the maximum in flexibility.



Standard electrical connection	
Heating type	Electric
Electrical connection	3N AC 380-415V 50-60HZ
Heater rating in kW	30
Total connected load in kW	31
Fuse rating in A	63
Water connection/drainage	
Cold water [number]	2x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	1643
External dimensions, width in mm	1089
External dimensions, depth in mm	1280
External dimensions, gross height in mm	1710
External dimensions, gross width in mm	1336
External dimensions, gross depth in mm	1530
Net weight in kg	648
Gross weight in kg	699
Maximum floor load in N	9206
Emissions data	
Emission sound pressure level in the workplace	73 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	6.1
Features	
Patented pre-spin	•
Cloth reprocessing	•
Imbalance monitoring	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Communication slot	•
Efficient fast spin cycle	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	96

PW 6321 [EL]

Washing machine, electrically heated

With individually programmable controls for the maximum in flexibility.



Connection options	
Payment system (optional)	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak-load negotiation / energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Respirator masks [number]	26
Overalls [number]	6
Over jackets [number]	9
Chemical protection suits [number]	5
Synthetic duvets [number]	4
Synthetic pillows [number]	8
Down duvets [number]	4
Down pillows [number]	8
Cloths, 22 g [number]	727
Cotton mops, 40 cm / 190 g [number]	168
Cotton mops, 50 cm / 220 g [number]	145
Microfibre mops, 40 cm / 120 g [number]	267
Microfibre mops, 50 cm / 170 g [number]	188
Summer horse blankets [number]	5
Standards, test certificates and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

PW 6321 [EL MF]

Washing machine, electrically heated

With liquid dispenser and individually programmable controls.



EAN: 4002516447467 / Article number: 51632109NER / Material number: 11814050

Construction type and version	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:10
Load in kg	32
Drum volume in l	320
Door opening [Ø] in mm	430
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Stainless steel honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•

- Drum volume 320 l, load size 32 kg
- Large programme variety - application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient - low water and energy consumption
- Perfect spinning results – residual moisture 47 %, g-factor 447

PW 6321 [EL MF]

Washing machine, electrically heated

With liquid dispenser and individually programmable controls.



Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in l/kg	9
Specific energy consumption for cold water connection in kWh/kg	0.25
Specific water consumption for hot water connection in l/kg	8.8
Specific energy consumption for hot water connection in kWh/kg	0.1
Water consumption with cold water connection in l	288
Energy consumption with cold water connection in kW	8
Programme duration in minutes with cold water connection	61
Water consumption with hot water connection in l	281.6
Energy consumption with hot water connection in kW	3.2
Programme duration in minutes with cold water and hot water connection	49
Water consumption in ECO programme with cold water connection in l	281.6
Energy consumption in ECO programme with cold water connection in ECO programme	6.2
Programme duration in minutes with cold water connection in ECO programme	47
Water consumption in ECO programme with hot water connection in l	284.8
Energy consumption in ECO programme with hot water connection in ECO programme	1.6
Programme duration in minutes with cold water and hot water connection in ECO programme	37
Residual moisture with cold rinse in %	50
Residual moisture with hot rinse in %	47
Spin speed in rpm	1000
g factor	447
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Dispensing	
Detergent drawer	3 compartments
Liquid dispensing module	•
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•

PW 6321 [EL MF]

Washing machine, electrically heated

With liquid dispenser and individually programmable controls.



Standard electrical connection	
Heating type	Electric
Electrical connection	3N AC 380-415V 50-60HZ
Heater rating in kW	30
Total connected load in kW	31
Fuse rating in A	63
Water connection/drainage	
Cold water [number]	2x 1/2" hose w/ 3/4" th. union
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	1643
External dimensions, width in mm	1089
External dimensions, depth in mm	1280
External dimensions, gross height in mm	1710
External dimensions, gross width in mm	1336
External dimensions, gross depth in mm	1530
Net weight in kg	648
Gross weight in kg	699
Maximum floor load in N	9206
Emissions data	
Emission sound pressure level in the workplace	73 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	6.1
Features	
Patented pre-spin	•
Cloth reprocessing	•
Imbalance monitoring	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Communication slot	•
Efficient fast spin cycle	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	96

PW 6321 [EL MF]

Washing machine, electrically heated

With liquid dispenser and individually programmable controls.



Connection options	
Payment system (optional)	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak-load negotiation / energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Respirator masks [number]	26
Overalls [number]	6
Over jackets [number]	9
Chemical protection suits [number]	5
Synthetic duvets [number]	4
Synthetic pillows [number]	8
Down duvets [number]	4
Down pillows [number]	8
Cloths, 22 g [number]	727
Cotton mops, 40 cm / 190 g [number]	168
Cotton mops, 50 cm / 220 g [number]	145
Microfibre mops, 40 cm / 120 g [number]	267
Microfibre mops, 50 cm / 170 g [number]	188
Summer horse blankets [number]	5
Standards, test certificates and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited
Fairacres
Marcham Road
Abingdon
OX14 1TW

Sales: 0845 365 6636
Customer Service: 0845 365 6608
miele-professional@miele.co.uk
www.miele.co.uk/professional
Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment.
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.