Miele Professional PWM 916 Washing Machine



PWM 916 [EL DV DD]

Professional washing machine, electric heating with detergent drawer, M Touch Pro Plus – freely programmable.



- Drum volume 140 I, load size 16 kg
- Top cleaning & consumption values
 innovative Miele technology
- Ideal operation thanks to colour touch display M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

EAN: 4002516435969 / Article number: 51916001GB / Material number: 11779760

Construction type and version	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:9
Load in kg	16
Drum volume in I	140
Door opening [Ø] in mm	415
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented stainless steel honeycomb drum 2.0	•
Application	
Suitable for the hotel and catering industry	<u> </u>
Suitable for retirement and care homes	<u> </u>
Suitable for facility management	•
Suitable for launderettes	<u> </u>
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•

PWM 916 [EL DV DD]



Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/kg	6.2
Specific energy consumption for cold water connection in kWh/kg	0.14
Specific water consumption for hot water connection in I/kg	5.9
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in I	99.2
Water consumption for cold water connection in Mops standard 60 °C programme in I	182.2
Energy consumption with cold water connection in kW	2.24
Energy consumption for cold water connection in Mops standard 60 °C programme in kWh	3.21
Programme duration in minutes with cold water connection	49
Water consumption with hot water connection in I	94.4
Water consumption for hot water connection in Mops standard 60 °C programme in I	178.1
Energy consumption with hot water connection in kW	0.96
Energy consumption for hot water connection in Mops standard 60 °C programme in kWh	1.33
Programme duration in minutes with cold water and hot water connection	43
Water consumption in ECO programme with cold water connection in I	92.8
Energy consumption in ECO programme with cold water	1.6
Programme duration in minutes with cold water connection in ECO programme	34
Water consumption in ECO programme with hot water connection in I	91.2
Energy consumption in ECO programme with hot water	0.48
Programme duration in minutes with cold water and hot water connection in ECO programme	32
Programme running time in minutes for Mops standard 60 °C programme with cold water connection	53
Programme running time in minutes for Mops standard 60 °C programme with hot water connection	47
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	44
Residual moisture when processing cleaning cloths in %	25
Spin speed in rpm	1075
g factor	462
Tested operating hours	30000

Miele

PWM 916 [EL DV DD]



Control system	
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Option to enter weight prior to start of programme	•
Dispensing	
Detergent drawer	3 compartments
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•
Standard electrical connection	
Heating type	Electric
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	14
Total connected load in kW	14.6
Fuse rating in A	25
Possible voltage variant 1	
Electrical connection	3N AC 400V 60HZ
Heater rating in kW	14
Total connected load in kW	14.6
Fuse rating in A	25
Water connection/drainage	
Cold water [number]	3 x 1/2" hose w/ 3/4" unior
Hot water [number]	1x 1/2" hose w/ 3/4" th. union
Hard water (optional) [number]	2 x 1/2" w/ 3/4" union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	1450
External dimensions, width in mm	924
External dimensions, depth in mm	835
External dimensions, gross height in mm	1585
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1130
Net weight in kg	337
Gross weight in kg	357
Maximum floor load in N	5091
Emissions data	
Emission sound pressure level in the workplace	65 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	6.48

PWM 916 [EL DV DD]



Features	
Patented pre-spin	•
Cloth reprocessing	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Weighing plinth (optional)	•
Add laundry	•
Programme selection via colour frame	•
Efficient fast spin cycle	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	92
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
Water recovery (optional)	•
LAN	•
WiFi	•
Connector Box	•

PWM 916 [EL DV DD]



Capacities	
Respirator masks [number]	13
Helmets [number]	4
Overalls [number]	2
Over jackets [number]	3
Chemical protection suits [number]	1
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	1
Down pillows [number]	3
Cloths, 22 g [number]	355
Cotton mops, 40 cm / 190 g [number]	82
Cotton mops, 50 cm / 220 g [number]	71
Microfibre mops, 40 cm / 120 g [number]	130
Microfibre mops, 50 cm / 170 g [number]	91
Mops, office, 100 g [quantity]	160
Mops, stairway, 150 g [quantity]	105
Summer horse blankets [number]	3
Standards, test certificates and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•



The Miele Company Limited Fairacres Marcham Road Abingdon OX14 1TW

Sales: 0845 365 6636

Customer Service: 0845 365 6608 miele-professional@miele.co.uk www.miele.co.uk/professional

Twitter: @MieleProf

Professional laundry, dishwashing, disinfection and sterilisation equipment. For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.