

**Miele**

# JTM Service - Miele Professional PDR 516 Slimline Brochure



## PDR 516 SL ROP [EL GS]

Vented dryer, galvanised sides, electrically heated

In SlimLine design, with residual moisture controls for perfect drying results.



- Drum volume 300 l, load size 12 kg–16 kg
- Very easy installation - only 711 mm wide
- Easy to move - direct access underneath
- Shortest cycles thanks to diagonal air flow
- Precision drying of all fabrics – PerfectDry

EAN: 4002516659600 / Article number: 52516003GB / Material number: 12262550

<b>Construction type and version</b>	
Construction type	SlimLine
Range	Performance
Front	Iron grey
Fascia color	Stainless steel
Load size with a load ratio of 1:25	12
Load size with a load ratio of 1:18	16
Drum volume in l	300
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Stainless steel drum	•
<b>Application</b>	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundries	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	12.5
Specific energy consumption in kWh/kg	0.55
Programme duration in min.	31
<b>Control system</b>	
Control system	M Select Benchmark
Programmability	Setting of defined parameters
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Control panel with easy-to-understand symbols	•
<b>Standard electrical connection</b>	
Heating type	Electric
Electrical connection	3N AC 400V 50/60HZ
Electric heater rating in kW	13.5
Total connected load in kW	14.1
Fuse rating in A	25

## PDR 516 SL ROP [EL GS]

Vented dryer, galvanised sides, electrically heated

In SlimLine design, with residual moisture controls for perfect drying results.



<b>Dimensions and weight of dryer</b>	
External dimensions, height in mm	1800
External dimensions, width in mm	711
External dimensions, depth in mm	1089
External dimensions, gross height in mm	1810
External dimensions, gross width in mm	800
External dimensions, gross depth in mm	1180
Net weight in kg	145.7
Gross weight in kg	159
Maximum floor load in N	1664
<b>Emissions data</b>	
Emission sound pressure level in the workplace	55 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.7
<b>Features</b>	
Intelligent drum reversal	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Retractable plinth	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	96
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
WiFi	•
Connector Box	•
LAN module (optional)	•
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

## PDR 516 SL ROP [G GS]

Vented dryer, galvanised sides, gas heated

In SlimLine design, with residual moisture controls for perfect drying results.



- Drum volume 300 l, load size 12 kg–16 kg
- Very easy installation - only 711 mm wide
- Easy to move - direct access underneath
- Shortest cycles thanks to diagonal air flow
- Precision drying of all fabrics – PerfectDry

EAN: 4002516659754 / Article number: 52516005GB / Material number: 12262910

<b>Construction type and version</b>	
Construction type	SlimLine
Range	Performance
Front	Iron grey
Fascia color	Stainless steel
Load size with a load ratio of 1:25	12
Load size with a load ratio of 1:18	16
Drum volume in l	300
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Stainless steel drum	•
<b>Application</b>	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for commercial laundries	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	14.5
Specific energy consumption in kWh/kg	0.65
Programme duration in min.	27
<b>Control system</b>	
Control system	M Select Benchmark
Programmability	Setting of defined parameters
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Control panel with easy-to-understand symbols	•
<b>Standard electrical connection</b>	
Heating type	Gas
Electrical connection	1N AC 230V 50/60HZ
Gas heater rating in kW	18
Total connected load in kW	0.6
Fuse rating in A	10

## PDR 516 SL ROP [G GS]

Vented dryer, galvanised sides, gas heated

In SlimLine design, with residual moisture controls for perfect drying results.



<b>Dimensions and weight of dryer</b>	
External dimensions, height in mm	1800
External dimensions, width in mm	711
External dimensions, depth in mm	1089
External dimensions, gross height in mm	1810
External dimensions, gross width in mm	800
External dimensions, gross depth in mm	1180
Net weight in kg	149.7
Gross weight in kg	163
Maximum floor load in N	1704
<b>Emissions data</b>	
Emission sound pressure level in the workplace	56 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.7
<b>Features</b>	
Intelligent drum reversal	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Retractable plinth	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	93
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
WiFi	•
Connector Box	•
LAN module (optional)	•
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
DVGW gas	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited  
Fairacres  
Marcham Road  
Abingdon  
OX14 1TW

Sales: 0845 365 6636  
Customer Service: 0845 365 6608  
[miele-professional@miele.co.uk](mailto:miele-professional@miele.co.uk)  
[www.miele.co.uk/professional](http://www.miele.co.uk/professional)  
Twitter: @MieleProf

**Professional laundry, dishwashing, disinfection and sterilisation equipment.**  
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.