

**Miele**

JTM Service - Miele Professional PDR 922 Tumble  
Dryer Brochure - Electric, Gas, Steam & Hot Water



PDR 922 [EL]

Professional vented dryer, electric heating  
with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 400 l, load size 16 kg–22 kg
- Unique, gentle fabric care – honeycomb drum
- Greatest energy efficiency thanks to Air Recycling
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516443483 / Article number: 52922002EU / Material number: 11795620

<b>Construction type and version</b>	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Load size with a load ratio of 1:25	16
Load size with a load ratio of 1:18	22
Drum volume in l	400
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	22.3
Specific energy consumption in kWh/kg	0.5
Programme duration in min.	23
Service life in drying cycles	40000

PDR 922 [EL]

Professional vented dryer, electric heating  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Control system</b>	
Control system	M Touch Pro
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
<b>Standard electrical connection</b>	
Heating type	Electric
Electrical connection	3N AC 400V 50/60HZ
Electric heater rating in kW	22.5
Total connected load in kW	23.5
Fuse rating in A	50
<b>Dimensions and weight of dryer</b>	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1162
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1254
Net weight in kg	198.9
Gross weight in kg	213
Maximum floor load in N	2275
<b>Emissions data</b>	
Emission sound pressure level in the workplace	62 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2.6
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling Flex	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	91

PDR 922 [EL]

Professional vented dryer, electric heating  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
WiFi	•
Connector Box	•
LAN module (optional)	•
<b>Capacities</b>	
Respirator masks [number]	16
Overalls [number]	3
Over jackets [number]	5
Synthetic duvets [number]	2
Synthetic pillows [number]	3
Down duvets [number]	2
Down pillows [number]	4
Cloths, 22 g [number]	364
Cotton mops, 40 cm [number]	84
Cotton mops, 50 cm [number]	73
Microfibre mops, 40 cm [number]	133
Microfibre mops, 50 cm [number]	94
Summer horse blankets [number]	3
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

PDR 922 [G]

Professional vented dryer, gas heating  
with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 400 l, load size 16 kg–22 kg
- Unique, gentle fabric care – honeycomb drum
- Precision drying of all fabrics – PerfectDry
- Greatest energy efficiency thanks to Air Recycling
- Connected for the future using LAN and WiFi

EAN: 4002516409366 / Article number: 52922003EU / Material number: 11718590

<b>Construction type and version</b>	
Construction type	Front loader
Range	Performance Plus
Front	Iron grey
Load size with a load ratio of 1:25	16
Load size with a load ratio of 1:18	22
Drum volume in l	400
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for laundrettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	21.7
Specific energy consumption in kWh/kg	0.53
Programme duration in min.	25
Service life in drying cycles	40000

PDR 922 [G]

Professional vented dryer, gas heating  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Control system</b>	
Control system	M Touch Pro
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
<b>Standard electrical connection</b>	
Heating type	Gas
Electrical connection	1N AC 230V 50HZ
Gas heater rating in kW	21.5
Total connected load in kW	1
Fuse rating in A	10
<b>Dimensions and weight of dryer</b>	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1162
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1254
Net weight in kg	203.9
Gross weight in kg	218
Maximum floor load in N	2324
<b>Emissions data</b>	
Emission sound pressure level in the workplace	62 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2.6
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•

PDR 922 [G]

Professional vented dryer, gas heating  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
WiFi	•
Connector Box	•
LAN module (optional)	•
<b>Capacities</b>	
Respirator masks [number]	16
Overalls [number]	3
Over jackets [number]	5
Synthetic duvets [number]	2
Synthetic pillows [number]	3
Down duvets [number]	2
Down pillows [number]	4
Cloths, 22 g [number]	364
Cotton mops, 40 cm [number]	84
Cotton mops, 50 cm [number]	73
Microfibre mops, 40 cm [number]	133
Microfibre mops, 50 cm [number]	94
Summer horse blankets [number]	3
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
DVGW gas	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

## PDR 922 [SI]

Professional vented dryer, steam heating  
with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 400 l, load size 16 kg–22 kg
- Unique, gentle fabric care – honeycomb drum
- Precision drying of all fabrics – PerfectDry
- Greatest energy efficiency thanks to Air Recycling
- Connected for the future using LAN and WiFi

EAN: 4002516443513 / Article number: 52922013EU / Material number: 11795700

<b>Construction type and version</b>	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Load size with a load ratio of 1:25	16
Load size with a load ratio of 1:18	22
Drum volume in l	400
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
<b>Performance data</b>	
Maximum evaporation capacity in l/hour	15
Specific energy consumption in kWh/kg	0.61
Programme duration in min.	29
Service life in drying cycles	40000



PDR 922 [SI]

Professional vented dryer, steam heating  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Control system</b>	
Control system	M Touch Pro
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
<b>Standard electrical connection</b>	
Heating type	Indirect steam
Electrical connection	1N AC 230V 50/60HZ
Steam heater rating in kW	28
Total connected load in kW	1
Fuse rating in A	10
<b>Dimensions and weight of dryer</b>	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1162
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1254
Net weight in kg	231.9
Gross weight in kg	246
Maximum floor load in N	2600
<b>Emissions data</b>	
Emission sound pressure level in the workplace	62 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2.6
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecyclingPlus	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
<b>Efficiency and sustainability</b>	
Recycling rate in %	91

PDR 922 [SI]

Professional vented dryer, steam heating  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
WiFi	•
Connector Box	•
LAN module (optional)	•
<b>Capacities</b>	
Respirator masks [number]	16
Overalls [number]	3
Over jackets [number]	5
Synthetic duvets [number]	2
Synthetic pillows [number]	3
Down duvets [number]	2
Down pillows [number]	4
Cloths, 22 g [number]	364
Cotton mops, 40 cm [number]	84
Cotton mops, 50 cm [number]	73
Microfibre mops, 40 cm [number]	133
Microfibre mops, 50 cm [number]	94
Summer horse blankets [number]	3
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

PDR 922 [HW]

Professional vented dryer, heated with hot water  
with programmable M Touch Pro controls for the maximum in flexibility.



- Unique, gentle fabric care – honeycomb drum
- Excellent energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics – PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516409137 / Article number: 52922005EU / Material number: 11718230

<b>Construction type and version</b>	
Construction type	Front loader
Range	Performance Plus
Front	Iron grey
Load size with a load ratio of 1:25	16
Drum volume in l	400
Drying system	Hot water
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	•
<b>Application</b>	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
<b>Performance data</b>	
Specific energy consumption in kWh/kg	0.56
Programme duration in min.	60
Service life in drying cycles	40000
<b>Control system</b>	
Control system	M Touch Pro
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•

## PDR 922 [HW]

Professional vented dryer, heated with hot water  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Standard electrical connection</b>	
Heating type	Hot water
Electrical connection	1N AC 230V 50/60HZ
Heater rating, hot water in kW	9.8
Total connected load in kW	1
Fuse rating in A	10
<b>Dimensions and weight of dryer</b>	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1162
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1254
Net weight in kg	231.9
Gross weight in kg	246
Maximum floor load in N	2600
<b>Emissions data</b>	
Emission sound pressure level in the workplace	62 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2.6
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecyclingPlus	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
<b>Connection options</b>	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
WiFi	•
Connector Box	•
LAN module (optional)	•

PDR 922 [HW]

Professional vented dryer, heated with hot water  
with programmable M Touch Pro controls for the maximum in flexibility.



<b>Capacities</b>	
Respirator masks [number]	16
Overalls [number]	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	2
Down pillows [number]	2
Cloths, 22 g [number]	364
Cotton mops, 40 cm [number]	58
Cotton mops, 50 cm [number]	51
Microfibre mops, 40 cm [number]	93
Microfibre mops, 50 cm [number]	65
Summer horse blankets [number]	3
<b>Standards, test certificates and symbols</b>	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•

The Miele Company Limited  
Fairacres  
Marcham Road  
Abingdon  
OX14 1TW

Sales: 0845 365 6636  
Customer Service: 0845 365 6608  
[miele-professional@miele.co.uk](mailto:miele-professional@miele.co.uk)  
[www.miele.co.uk/professional](http://www.miele.co.uk/professional)  
Twitter: @MieleProf

**Professional laundry, dishwashing, disinfection and sterilisation equipment.**  
For many years Miele Professional has been at the forefront of manufacturing commercial laundry, dishwashing, disinfecting and sterilisation equipment, bringing you a comprehensive selection of machines for a wide range of applications. Whatever the business sector our commercial range has it covered.