

SPD522S

Family	Professional dishwasher
Subfamily	Undercounter
Type	Undercounter dishwashers
Crockery	Crockery; Glasses; Cutlery; GN1/1 trays
Double basket	Yes
Basket dimensions	500x500 mm
Control panel	Touch screen
Rinse pump	Self-Adaptive HTR+
Wash pump	Variable speed AdaptWash
Power connection	400 V 3N~ / 15 A / 8,4 kW / 50 Hz
Product dimensions (WxDxH)	600x600x822 mm



Target

Industries	Bar / Cafeterias / Bistros / Wine bars / Pubs; Hotels; Ristoranti / Catering; Bakeries / Pastry shops; Care facilities ; Commercial food services; Grocery shops / Food retail
-------------------	--

Aesthetics

Led color	White	Series	Pura
------------------	-------	---------------	------

Technical Features

Trays number	7 x GN 1/1 (530 x 325 mm)	Max water hardness	54°f - 30°dH
Trays washing option	Yes	Inlet pressure	100-1000 kPa (min-max)
Water consumption per cycle	2,5 l	Detergent load	1,5 l/h
Wash temperature (min-max)	60 °C - 70 °C	Rinse load	0,4 l/h
Rinse temperature (min-max)	65 °C - 87 °C	Usable load height	400 mm
Min. water connection temperature	5°C	Depth with open door	1020 mm
Minimum water consumption per cycle	1,8 l	Configuration 1: maximum height for glasses lower basket/ Ø dishes upper basket	110 mm/225 mm
Max. inlet temperature	60°C	Configuration 2: max H glasses lower basket /max Ø dishes upper basket	190 mm/145 mm

Programs

Programs	10 customizable programs; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program table	Pura dishwasher twin basket 500
Program visibility	Yes
Maximum basket/hour	90
Maximum dishes/hour	3240
Maximum glasses/hour	4320

Connectivity

 			
SmegConnect Pro	Yes	PST certificate support period [UK]	24 months
Connectivity	Wi-Fi	UK PSTI support period end date	2028-04-09

Electrical Connection

Tank heating element power	2000 W	Default connection	8400 W
Boiler heating element power	5700 W	Optional electrical connection	230 V 3~/24 A / 8,4 kW / 50 Hz; 230 V~/14 A / 3,1 kW / 50 Hz; 230 V~/31 A / 7,1 kW / 50 Hz
Wash pump power	700 W	Plug	Not present

Interface

Display	TFT	Detergent missing alert	Yes
On/Off button	Yes	Cycle progress alert	Yes
Salt alert	Yes	End-cycle alert	Yes
Rinse aid missing alert	Yes	Manual diagnostic	Yes

Construction

Tank	Deep drawn	Filter	5-stage filter system
Construction	Integral double-skin	Filter presence sensor	Yes
Tank material	Stainless steel AISI 304	Tank capacity	11 l
Back panel	Galvanized	Boiler capacity	6.5 l
Balanced door	Yes	Boiler type	Artmosferic boiler
Upper wash system	One wash and one split rinse spray arms, stainless steel	Noise	Lpa 54,5 dBA
		USB port	Yes
		Protection class	IPX4
		Adjustable feet	Yes
		Drain max. height	600 mm

Lower wash system	One wash and one split rinse spray arms, stainless steel
Tank filter	Stainless steel
Door gasket	On 3 sides
Rack guides	Embossed low, telescopic up

Accessories included


Dish basket	1x PB50D01	Water supply hose	Yes - 2 m
Cutlery basket	2x PHOOS01	Drain hose	Yes - 2m
Flat basket	1x PB50G02		

Equipments

Drain pump	Yes	Option for auto daily switch on	Yes, default OFF
Peristaltic detergent dispenser	Electronic control	Cycle counter	Yes
Peristaltic rinse-aid dispenser	Electronic control	Break tank	Yes
Chemicals level probe	Yes, with optional kit KITSONLIV	Partial renewal of water in the tank and built-in drain pump	Yes
Automatic built softener	Yes	Water supply pipe diameter	DN15 - 1/2"
Rinse boiler Thermostop system	Yes - default	Drain supply pipe diameter	DN20-G 3/4"
Wash tank Thermostop system	Yes	Detergent (red) hose length	2,2 m
Wash pump soft start system	Yes	Rinse aid (blue) hose length	2,2 m
Stand-by system	Yes		

Logistic Information

EAN code	8017709348496	Net weight	68.000 kg
Packed product dimensions (WxDxH)	990x660x700 mm	Gross weight	76.000 kg



Compatible Accessories

KITDETKCC500




Kit for detergent (1l) and rinse aid (1l) storage for double wall models



KITSONLIV

Probe level kit

PB50D01



Polypropylene basket for 18 plates
Ø250 mm max, dim. (WxDxH)
500x500x105 mm



PB50G01

Universal flat bottom polypropylene basket, internal height 73 mm, dim.
(WxDxH) 500x500x100 mm

PB50G02



Universal flat bottom polypropylene basket, internal height 150 mm, dim.
(WxDxH) 500x500x170 mm



PHOOS01

Polypropylene single basket for cutlery

PHOOS04



4 compartments polypropylene basket for cutlery



WB50D01

Wire basket for 18 dishes Ø250 mm max or trays h 370 mm, dim. (WxDxH)
500x500x92 mm

WB50G01



Universal wire basket with flat bottom, internal height 120 mm, dim. (WxDxH)
500x500x130 mm



WB50G02

Wire basket with sloped bottom for 25 glasses Ø90 mm max, dim.
(WxDxH) 500x500x170 mm

WB50G03



Wire basket with sloped bottom for glasses Ø72 mm max, dim. (WxDxH)
500x500x235 mm




WB50G04

Wire basket with flat bottom for 12 glasses Ø110 mm max, dim.
(WxDxH) 500x500x165 mm

WB50PG5



Wire basket with flat bottom for 25 plastic glasses, dim. (WxDxH)
500x500x260 mm



WB50T02

Wire basket for 7 trays GN1/1 h 20 mm, dim. (WxD) 500x500 mm

WH00S01



Wire insert for 17 small dishes, width 100 mm, for flat bottom baskets
500x500 and 600x500 mm



WS5

Stainless steel underframe for undercounter glasswashers and dishwashers 500 mm, dim. (WxDxH)
595x595x490 mm

Symbols glossary

 A0=30	THERMODESINFECTION A0=30	 A0=60	THERMODESINFECTION A0=60
 GN1/1	SUITABLE FOR GASTRONORM TRAY		HTR RINSING SYSTEM
 Wi-Fi connectivity			MAX. USABLE HEIGHT 400mm
 5 STAGE FILTER			Professional appliance with Wi-fi connectivity and remote control via Remote SmegConnectPro App.

Benefit (TT)

Balanced door

Effortless opening and closing

The counterbalanced door is designed to ensure smooth and effortless opening and closing, providing high user convenience. Additionally, it can be locked in a halfway position, a particularly useful feature for promoting natural drying at the end of the workday, enhancing overall hygiene and preventing the buildup of residual moisture.

5-stage system

Deep cleaning and spotless washes with the patented filtration system

The innovative Smeg filtration system consists of 5 stages to completely eliminate all impurities: the 1st stage captures larger food residues; in the 2nd and 3rd stages, finer particles are captured at this filtration stage; the 4th stage features a pre-filtration grid to prevent debris from entering the tank and clouding the water. Finally, the last stage is designed to further protect the washing and draining pumps from any debris that may accidentally enter the tank during filter cleaning.

HTR+ System

Self-adaptive rinsing system for intelligent water management

The self-Adaptive HTR+ System monitors and adjusts the rinse volume with each wash cycle. The intelligent rinse management ensures the perfect amount of water and heat on the dishes, delivering consistent, reliable results, cycle after cycle.

Moulded tank

Superior washing performance and enhanced cleaning convenience with molded tub bottoms and basket guides

Smeg dishwashers are designed with moulded tank and basket guides. The absence of sharp edges ensures an optimised wash flow, guaranteeing hygiene and impeccable cleaning performance. Furthermore, this innovative design simplifies machine cleaning, reducing the need for maintenance interventions.

Integrated softener

Effective water treatment for consistently sparkling glasses

The integrated continuous regeneration water softener ensures effective water treatment, enhancing washing performance and preserving the machine's operational lifespan. The resin regeneration process takes place during the wash cycle without interruptions, providing constant control over water hardness. This system prevents limescale buildup, maximises detergent efficiency, and guarantees spotless results on glassware and dishes.

Integral double-skin

Thermal and acoustic insulation guaranteed

The double-skin design of undercounter dishwashers is engineered to optimise energy efficiency by minimising heat loss and accelerating water heating, resulting in lower energy consumption and faster start-up times. Additionally, it provides effective sound insulation, helping to reduce noise levels and ensuring a quieter, more comfortable working environment for staff.

Drain pump

Partial water replacement during the wash cycle for clean and hygienic dishes

The standard drain pump, equipped with a partial water exchange system, ensures that the dirtiest water is automatically removed at every wash cycle. This mechanism allows for continuous renewal of the water used, ensuring that each phase of the washing process is carried out with clean water. The result is optimal dishwashing performance, with outstanding efficiency and an impeccable level of hygiene.

Soft-start system

Effective management of the washing pump to protect your glassware

The Soft-Start function initiates the wash cycle gently and gradually, progressively increasing the water pressure. This system has been designed to provide optimal protection for the most fragile items, such as crystal glasses, significantly reducing the risk of chipping or damage. At the same time, it ensures excellent cleaning performance, combining efficiency and safety in every wash cycle.

MyPersonal Wash

10 pre-set washing programmes for a complete and ready-to-use solution

Each model in the PURA range offers 10 tested programmes, ensuring ready-to-use solutions for any washing requirement. With the MyPersonal Wash function, parameters such as time, temperature, pressure, and washing options can be customised, optimising cycles for delicate dishes or stubborn dirt. The result is a tailored wash, always flawless.

AdaptWash system

Consistently perfect washing pressure for flawless results with every wash

The AdaptWash system offers 3 pressure levels that automatically adjust based on the selected program, ensuring optimal cleaning for every type of load.

Program visibility

Program selection displayed for simplified dishwasher management

Users can select the programs to be displayed, hiding those that are unnecessary or unused. This feature not only helps prevent improper use of the appliance but also represents a significant step towards fully customising the user experience.

Double basket

Double load capacity for maximum productivity

Designed to ensure maximum productivity and high configuration flexibility. This solution represents a sustainable choice, as it allows for handling larger loads while reducing the number of cycles required. In doing so, it optimises the use of resources such as energy, water, and detergents.